




JOINT DETAIL



CORD DIA. = 1"
VOLUME = 2950cc

"O" RING GASKET




TONGUE END

BELL END

NOTES:

1. WATER TIGHT JOINTS MADE IN ACCORDANCE WITH ASTM C76/C443/C361 & C655, GREENBOOK S 207-2 AND CALTRANS S 65 REQUIREMENTS.
2. LAYING LENGTHS 8' & 4' AS REQUIRED.
3. ALL CONCRETE USED IN THE MANUFACTURE OF RCP PRODUCTS CONTAINS TYPE II/V CEMENT PORTLAND CEMENT CONFORMING TO ASTM C-150.

4. AVERAGE JOINT GAP IS 0.04" (1/2").
5. STEEL REINFORCEMENT NOT SHOWN.
6. ALL DIMENSIONS SUBJECT TO ALLOWABLE SPECIFICATION TOLERANCES AND PARAMETERS.
7. BEVEL PIPE FOR 45 RADIUS MINIMUM.



- LBS / 8' JNT = 19,280,
 - LBS / 4' JNT = 9,640
 - LBS / LF = 2,410
- SHIPPING INFO. / FULL TRUCKLOAD (8' JOINTS) :
- JOINTS = 2
 - LF = 16
 - WEIGHT = 38,560 LBS PAYLOAD



3011 NORTH LAUREL AVE. RIALTO, CA 92377

JOB NAME: STANDARD PRODUCT

LOCATION: TBD

84" REINFORCED CONCRETE PIPE / CONFINED "O"-RING JOINT
STANDARD DRAWING FOR DRYCAST

DRAWN BY
FB
DRAWING NUMBER

CHECKED BY
KB

PART NO.
08400080000R000

DATE
10/17/2016

ORING_84inRCP_07242012

DRAWING SCALE (UNO)
N.T.S.

SHEET
1 OF 1