





JOINT DETAIL



NOTES:

1. WATER TIGHT JOINTS MADE IN ACCORDANCE WITH ASTM C76/C443/C361 & C655, GREENBOOK S 207-2 AND CALTRANS S 65 REQUIREMENTS.
2. LAYING LENGTHS 8' & 4' AS REQUIRED.
3. ALL CONCRETE USED IN THE MANUFACTURE OF RCP PRODUCTS CONTAINS TYPE II/V CEMENT PORTLAND CEMENT CONFORMING TO ASTM C-150.

4. AVERAGE JOINT GAP IS 0.04" (1/2").
5. STEEL REINFORCEMENT NOT SHOWN.
6. ALL DIMENSIONS SUBJECT TO ALLOWABLE SPECIFICATION TOLERANCES AND PARAMETERS.
7. BEVEL PIPE FOR 45 RADIUS MINIMUM.



- LBS / 8' JNT = 24,560
- LBS / 4' JNT = 12,280
- LBS / LF = 3,070

SHIPPING INFO. / FULL TRUCKLOAD (8' JOINTS) :

- JOINTS = 2
- LF = 16
- WEIGHT = 49,120 LBS PAYLOAD

THOMPSON™ PIPE GROUP LOS ANGELES	JOB NAME: STANDARD PRODUCT	90" REINFORCED CONCRETE PIPE / CONFINED "O"-RING JOINT STANDARD DRAWING FOR DRYCAST				DRAWING SCALE (UNO) N.T.S.
LOCATION: TBD	DRAWN BY FB	CHECKED BY KB	PART NO. 0900008000R000	DATE 10/14/2016		
	DRAWING NUMBER ORING_90inRCP_07242012				SHEET 1 OF 1	